

DIGITAL ANEMOMETER B-201

- 0.4 30 m/s
- 5 UNITS OF
 - **MEASUREMENT**
- COLOR DISPLAY
- **TEMPERATURE**

ACCURATE

HIGH QUALITY

RELIABLE

DURABLE

EASY TO READ

STURDY

SAFETY

CE COMPLIANT

RoHS COMPLIANT



B-201

THERMO-ANEMOMETER

















INTRODUCTION

The Beetech Anemometer B-401 measures the speed and pressure of the wind.

This Anemometer is reliable and high in Accuracy. It has a quick response time. It offers Over Range Detection and Low **Battery Indication**

It comes along with 1 Year Warranty against manufacturing defect. Each instrument is completely checked, tested and then provided to the user.

FEATURES

- Selectable measurement units:
- 1. m/s
- 2. Ft/min
- 3. MPH
- 4. Km/hr
- 5. Knots
- Fast Sampling Rate
- Max / Min / Data Hold Over Range Indication
- Low Battery Indication
 - Enable / Disable Auto Power Off

APPLICATION

Beetech B-401 is widely used in/by:

- Weather Stations
- Drone users
- Iron and Steel Industry
- HVAC Industry / Fan manufacturers
- Heating Systems
- Mining Industry
- Sporting event / Long Range Shooters
- Petrochemical Industry
- Pilots / Sky divers
- Aero-dynamics

SPECIFICATIONS		
Range	Resolution	Accuracy
0.4~30.0 m/s	0.1 m/s	±3%±0.3m/s
1.4~108 km/h	0.1 km/h	±3%±1.0km/H
0.9~67.0 f Mph	0.1 Mph	±3%±0.4 Mph
0.8~58.0 Knots	0.1 Knots	±3%±0.4 Knots
80~5900 ft/min	1.0 ft/min	±3%±40 ft/min
-20~70°C/-4~158°F		
±1.5°C/2.7°F		
O.1		
300ms		
-20°C ~ 60°C, -4°F ~ 140°F, 10%RH ~ 90%RH		
-20°C ~ 60°C, -4°F ~ 140°F, 10%RH ~ 75%RH		
3*1.5V "AAA" batteries		
Approximately 60 hours		
	Range 0.4~30.0 m/s 1.4~108 km/h 0.9~67.0 f Mph 0.8~58.0 Knots 80~5900 ft/min -20~70°C/-4~158°F ±1.5°C/2.7°F 0.1 300ms -20°C ~ 60°C, -4°F ~ 140°F, 10% 3*1.5V "AAA" batteries	RangeResolution0.4~30.0 m/s0.1 m/s1.4~108 km/h0.1 km/h0.9~67.0 f Mph0.1 Mph0.8~58.0 Knots0.1 Knots80~5900 ft/min1.0 ft/min-20~70°C/-4~158°F±1.5°C/2.7°F0.1300ms-20°C ~ 60°C, -4°F ~ 140°F, 10%RH ~ 90%RH-20°C ~ 60°C, -4°F ~ 140°F, 10%RH ~ 75%RH3*1.5V "AAA" batteries